



1. DELINEATORS TO BE MADE FROM 6061-T6 ALUMINUM ALLOY, 0.080 INCH THICK.
2. DELINEATOR TO EXTEND 1" ABOVE TOP OF POST.
3. DELINEATORS TO BE REFLECTORIZED WITH SILVER REFLECTIVE SHEETING. STRIPES TO BE PAINTED BLACK.
4. DELINEATORS TO BE PLACED ON POST SO THAT BOTTOM EDGE WILL BE 30" ABOVE THE TOP EDGE OF PAVEMENT NEAREST DELINEATOR.
5. DELINEATORS TO BE MOUNTED ON U-TYPE ROLLED-RAIL STEEL POSTS.
6. DELINEATOR SPACING TO BE DETERMINED BY CITY TRAFFIC ENGINEER.

<b>Chesapeake</b> VIRGINIA		<i>DESIGN AND CONSTRUCTION STANDARDS</i>	
		<b>ROAD EDGE</b>	
06/00/03	REV. FOR INTERNET 2003	DR. BY:	DATE:
DATE	<b>REVISIONS</b>	CHK. BY:	DATE:
		APP. BY:	DATE:

**B-2**

02

APPROVED FOR THE WEB \_\_\_\_\_  
City Engineer

/ /  
Date