

## **Division 32: Project Identification Signboard**

- 32.01 SCOPE:** This work shall consist of all labor, materials, and equipment necessary to provide project identification signboards. The signboards shall be 4 feet high by 8 feet long constructed at conspicuous locations on the job site where directed by the Engineer.
- 32.02 MATERIALS AND EXECUTION:** The field of the sign shall consist of one 4 foot by 8 foot sheet of grade B-B, medium density overlaid exterior plywood not less than 5/8 inch thick. The completed signboard shall be secured to two 4 inch by 4 inch posts with 10 penny nails, 6 inches on centers. The completed signboard shall be mounted with the bottom 4 feet above grade. The posts shall be set plumb, 4 feet into the ground and tamped tight. The posts shall be set 5 feet, 5 inches center to center. All lumber shall be B or better Southern pine, pressure-preservative treated with pentachlorophenol. All nails shall be aluminum or galvanized steel. The entire signboard and supports shall be given one coat of exterior oil primer and two coats of exterior oil paint. The lettering and sign work shall be performed by a skilled sign painter using pain known in the trade as bulletin colors. The 1 inch by 1 inch border shall be painted black and the lettering shall be single stroke using bulleting blue. The lettering style shall be “Gothic”, “Roman Capitols”, or “Thick and Thin” styles.
- 32.03 MEASUREMENT AND PAYMENT:** Project identification signboards will be measured and paid for per each sign and as specified in the Unit Price Table.

